

PHILIPS

HearLink

Technical data

Charger Plus

miniRITE T R

The Charger Plus for miniRITE T R is designed to be easy to use both at home and on-the-go. The charger's lid serves as protection and storage for the hearing aids, and the rechargeable built-in lithium-ion battery makes it possible to use the Charger Plus as a power bank, when no power supply is available.

Technical features

- Contains a power bank
- Designed to protect the hearing aids during transport
- Rubber feet for stability
- Shaped to accommodate different speaker lengths and earpiece types



For information on compatibility, please visit hearingsolutions.philips.com/charger-compatibility

Operating conditions

Temperature: +5°C to +38°C (+41°F to +100°F)
Humidity: 5% to 93% relative humidity,
non-condensing
Atmospheric pressure: 700 hPa to 1060 hPa

Transportation and storage conditions

Temperature and humidity shall not exceed the
mentioned limits for extended periods during
transportation and storage:

Transportation

Temperature: -20°C to +60°C (-4°F to 140°F)
Humidity: 5% to 93% relative humidity,
non-condensing
Atmospheric pressure: 700 hPa to 1060 hPa

Storage

Temperature: -20°C to +60°C (-4°F to 140°F)
Humidity: 5% to 93% relative humidity,
non-condensing
Atmospheric pressure: 700 hPa to 1060 hPa

Technical data

Name	Charger Plus miniRITE T R
Dimensions	H 76.4 mm / W 47.2 mm / L 95 mm
Weight	180 g
Colour	Black
Power cable	USB-A Detachable cable / 150 cm
Status indicator	LED light on charger when plugged to a power supply: Indicates charging status of the power bank. LED light on charger when disconnected from a power supply: Indicates the battery level of the power bank. LED light on hearing aids when charging: Indicates charging mode
Charging time of hearing aids	Max 3 hours depending on initial state of the battery Temperature: +10 °C to +35 °C (+50°F to +95°F) Max 4 hours depending on initial state of the battery Temperature: +5 °C to +10 °C (+41°F to +50°F) / +35 °C to +38 °C (+95°F to +100°F)
Charging time for the power bank battery	Max 4 hours charging depending on initial state of the battery Temperature: +10 °C to +35 °C (+50 °F to +95 °F)
Supplied power source unit	Included AC adapter
Charger input voltage	5 V DC
Charger input current	Max 1A (charging internal battery and 2 hearing instruments)
Connected to external equipment	When connected to external equipment plugged into a wall outlet, this equipment must comply with IEC-62368 or equivalent safety standards.
AC adapter input voltage	100-240 V AC
AC adapter input frequency	50-60 Hz
AC adapter output voltage	5 V DC
AC adapter output current	1 A



SBO Hearing A/S
Kongebakken 9
DK-2765 Smørum
Denmark

hearingsolutions.philips.com

