PHILIPS

Technical data
Charger Plus
nxtCIC R

The charger is designed for nxtCIC R hearing aids.
The charger uses contact charging and provides faster charging: Hearing aids are fully charged in 2 hours. It includes an integrated power bank for on-the-go charging.



Technical features

- Contact charging
- Contains a power bank
- Power bank capable of 3 full charges of the hearing aids
- Designed to protect the hearing aids during transport
- Rubber feet for stability
- Magnetic connection – ensures correct placement of hearing aids for charging
- Shaped to accommodate different earpiece types

For information on compatibility, please visit hearingsolutions.philips.com/charger-compatibility

Operating conditions
Temperature: +5°C to +40°C (+41°F to +104°F)
Humidity: 5% to 93% relative humidity, non-condensing
Atmospheric pressure: 700 hPa to 1060 hPa

Transportation and storage conditions
Temperature and humidity shall not exceed the mentioned limits during transportation and storage:

Transportation
Temperature: -20°C to +60°C (-4°F to +140°F)
Humidity: 5% to 93% relative humidity, non-condensing
Atmospheric pressure: 700 hPa to 1060 hPa

Storage
Temperature: -20°C to +30°C (-4°F to +86°F)
Humidity: 5% to 93% relative humidity, non-condensing
Atmospheric pressure: 700 hPa to 1060 hPa

Technical data

285248UK | 2026.09.30 | v2

Name	Charger Plus nxtCIC R
Dimensions	H 45 mm / W 96.5 mm / D 57.6 mm
Weight	85.1 g
Colour	Black
Power cable	USB-A to USB-C Detachable cable, length 150 cm
Status indicator	3 LEDs showing status from 0 to 100% LED light on charger when connected to a power supply: Indicates charging status of the power bank. LED light on charger when disconnected from a power supply: Indicates the battery level of the power bank. LED light on hearing aids when charging: Indicates charging mode
Charging time of hearing aids	Max 2 hours charging depending on initial state of the battery Temperature: +15°C to +35°C (+59°F to +95°F) Max 6 hours charging depending on initial state of the battery Temperature: +5°C to +15°C and +35°C to +40°C (+41°F to +59°F and +95°F to +104°F)
Charging time for the power bank battery	Max 4 hours charging depending on initial state of the battery Temperature: +15°C to +35°C (+59°F to +95°F)
Supplied power source unit	Included AC adapter
Charger input voltage	5 V DC
Charger input current	< 0.5 A
Connected to external equipment	When connected to included AC adapter, this equipment complies with IEC 62368-1 or equivalent safety standards.
AC adapter input voltage	100-240 V AC
AC adapter input frequency	50-60 Hz
AC adapter output voltage	5 V DC
AC adapter output current	1 A
Replaceable battery	Yes

SBO Hearing A/S
Kongebakken 9
DK-2765 Smørum
Denmark

hearingsolutions.philips.com

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. and are used under license. This product has been manufactured by or for and is sold under the responsibility of SBO Hearing A/S, and SBO Hearing A/S is the warrantor in relation to this product.