

PHILIPS

HearLink

Specification guide

HearLink 9030 | 7030 | 5030 | 3030 | 2030 miniBTE T R

HearLink miniBTE T R is a rechargeable behind-the-ear hearing instrument suitable for slight to severe hearing losses. Powered by AI sound technology, the HearLink miniBTE T R includes our most advanced audiological features in SoundMap 2. Thanks to updated Bluetooth® Low Energy, it directly connects to iOS (iPhone, iPad, iPod) and Android™ devices. The miniBTE T R comes with the miniFit thin tube system, which includes a wide variety of domes and custom molds.

Earhook



miniFit 1.3 mm






miniFit 0.9 mm



9030 | 7030 | 5030 | 3030 | 2030 MNB T R
(HEB9034, HEB7034, HEB5034, HEB3034, HEB2034)

Made for
iPhone | iPad | iPod

Works with
android



Technical features

- Direct audio streaming (compatible with iOS and Android™ devices)
- Hands-free communication**
- 2.4 GHz Bluetooth® Low Energy
- NFMI (near-field magnetic induction)
- Single push button
- Telecoil
- miniFit thin tube
- Hydrophobic coating
- IP68 rated
- LED visual indicator

Accessories*

- Philips HearLink app (compatible with iOS and Android™ devices)
- Philips HearLink Connect app (compatible with iOS and Android™ devices)
- Philips Remote Control
- Philips TV Adapter
- Philips AudioClip
- Noahlink Wireless (wireless programming interface)

* Please refer to hearingsolutions.philips.com for additional information and support.

** Available from FW 1.3 with select iPhone and iPad models.

Philips HearLink is a Made for iPhone, iPad, iPod hearing aid. Direct Audio Streaming for Android devices requires Android 10 or later, Bluetooth® 5.0 and an implementation of Audio Streaming for Hearing Aids (ASHA) on the Android device. For information on compatibility, please visit hearingsolutions.philips.com/compatibility.

Apple, the Apple logo, iPhone, iPad, iPod touch, and Apple Watch are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play, and the Google Play logo are trademarks of Google LLC.



The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Demant A/S is under license. Other trademarks and trade names are those of their respective owners.

HearLink 9030

HEB9034 MNB T R



- Earhook ··· miniFit 0.9 mm ··· miniFit 1.3 mm

2CC Coupler



	Earhook	miniFit 1.3 mm	miniFit 0.9 mm
OSPL90, Peak (dB SPL)	123	119	117
OSPL90, 1600 Hz (dB SPL)	120	114	108
OSPL90, HFA (dB SPL)	119	115	110
Full-on Gain, Peak (dB)	54	54	55
Full-on Gain, 1600 Hz (dB)	47	46	43
Full-on Gain, HFA (dB)	47	47	43
Reference Test Gain (dB)	41	36	33
Battery	Li-ion	Li-ion	Li-ion
Expected operating time, hours ¹⁾		24 h	
Distortion 500/800/1600 Hz (%)	<4/<3/<2	<4/<2/<2	<2/<2/<2
Frequency Range (Hz)	100-7300	100-6300	100-6800
Equivalent Input Noise ²⁾ (dB SPL)	17	19	21
Telecoil 1 mA/m 1000 Hz, ANSI (dB SPL)	78	84	84
Telecoil HFA SPLITS (dB SPL)	99	97	91

Ear simulator



	Earhook	miniFit 1.3 mm	miniFit 0.9 mm
OSPL90, Peak (dB SPL)	132	128	123
OSPL90, 1600 Hz (dB SPL)	127	122	116
OSPL90, HFA (dB SPL)	126	122	118
Full-on Gain, Peak (dB)	63	59	59
Full-on Gain, 1600 Hz (dB)	54	55	51
Full-on Gain, HFA (dB)	54	54	51
Reference Test Gain (dB)	47	46	40
Battery	Li-ion	Li-ion	Li-ion
Expected operating time, hours ¹⁾		24 h	
Distortion 500/800/1600 Hz (%)	<4/<4/<2	<5/<2/<2	<3/<2/<3
Frequency Range (Hz)	100-9500	100-8800	100-9500
Equivalent Input Noise ²⁾ (dB SPL)	19	16	19
Telecoil 1 mA/m 1600 Hz, IEC (dB SPL)	85	87	87

¹⁾ Expected operating time for rechargeable battery depends on use pattern, active feature set, hearing loss, sound environment, battery age and use of wireless accessories.

²⁾ Technical data measured with expansion, corresponding to the test box measurement settings.

"2cc" refers to a coupler according to IEC 60318-5:2006. "Ear simulator" refers to a coupler according to IEC 60318-4:2010.

Applied versions: IEC 60118-0 /A1:1994, IEC 60118-1 /A1:1998, IEC 60118-7: 2005, ANSI S3.22: 2014, IEC 60118-0:2015.

Full-on gain is measured with the gain control of the hearing instruments set to its full-on position minus 20 dB and with an input SPL of 70 dB.



This is to obtain a gain response equal to the full-on gain response from e.g. IEC 60118-0+A1:1994 but without influence of feedback.

HearLink 7030 | 5030 | 3030 | 2030

HEB7034, HEB5034, HEB3034, HEB2034 MNB T R



- Earhook --- miniFit 0.9 mm --- miniFit 1.3 mm

2CC Coupler



	Earhook	miniFit 1.3 mm	miniFit 0.9 mm
OSPL90, Peak (dB SPL)	123	119	117
OSPL90, 1600 Hz (dB SPL)	120	114	108
OSPL90, HFA (dB SPL)	119	115	110
Full-on Gain, Peak (dB)	54	54	55
Full-on Gain, 1600 Hz (dB)	47	46	43
Full-on Gain, HFA (dB)	47	47	43
Reference Test Gain (dB)	41	36	33
Battery	Li-ion	Li-ion	Li-ion
Expected operating time, hours ¹⁾	24 h		
Distortion 500/800/1600 Hz (%)	<4/<3/<2	<4/<2/<2	<2/<2/<2
Frequency Range (Hz)	100-7300	100-6300	100-6800
Equivalent Input Noise ²⁾ (dB SPL)	17	19	21
Telecoil 1 mA/m 1000 Hz, ANSI (dB SPL)	78	84	84
Telecoil HFA SPLITS (dB SPL)	99	97	91

Ear simulator



	Earhook	miniFit 1.3 mm	miniFit 0.9 mm
OSPL90, Peak (dB SPL)	132	128	123
OSPL90, 1600 Hz (dB SPL)	127	122	116
OSPL90, HFA (dB SPL)	126	122	118
Full-on Gain, Peak (dB)	63	59	59
Full-on Gain, 1600 Hz (dB)	54	55	51
Full-on Gain, HFA (dB)	54	54	51
Reference Test Gain (dB)	47	46	40
Battery	Li-ion	Li-ion	Li-ion
Expected operating time, hours ¹⁾	24 h		
Distortion 500/800/1600 Hz (%)	<4/<4/<2	<5/<2/<2	<3/<2/<3
Frequency Range (Hz)	100-7500	100-7500	100-7500
Equivalent Input Noise ²⁾ (dB SPL)	19	16	19
Telecoil 1 mA/m 1600 Hz, IEC (dB SPL)	85	87	87

¹⁾ Expected operating time for rechargeable battery depends on use pattern, active feature set, hearing loss, sound environment, battery age and use of wireless accessories.

²⁾ Technical data measured with expansion, corresponding to the test box measurement settings.

"2cc" refers to a coupler according to IEC 60318-5:2006. "Ear simulator" refers to a coupler according to IEC 60318-4:2010.

Applied versions: IEC 60118-0 /A1:1994, IEC 60118-1 /A1:1998, IEC 60118-7: 2005, ANSI S3.22: 2014, IEC 60118-0:2015.

Full-on gain is measured with the gain control of the hearing instruments set to its full-on position minus 20 dB and with an input SPL of 70 dB.

This is to obtain a gain response equal to the full-on gain response from e.g. IEC 60118-0+A1:1994 but without influence of feedback.

Feature overview

	HearLink 9030	HearLink 7030	HearLink 5030	HearLink 3030	HearLink 2030
SoundMap 2					
Amplification					
Frequency bandwidth	10 kHz	8 kHz	8 kHz	8 kHz	8 kHz
Extended Dynamic Range	●	●	–	–	–
Low Frequency Enhancement	●	●	●	●	●
Frequency Lowering	●	●	●	●	●
Comfort Control	4 options	2 options	–	–	–
Noise Control					
Speech Clarifier	3 options	2 options	–	–	–
Transition	4 options	3 options	2 options	●	●
Directionality					
Pinna	2 options	2 options	●	●	●
Fixed Directional	●	●	●	●	●
Adaptive Directionality	●	●	●	●	●
Dynamic Directionality	3 options	2 options	●	●	–
AI Noise Reduction					
Noise Reduction Mode	4 options	4 options	3 options	3 options	2 options
Special noise management					
Soft Noise Management	●	●	●	●	●
Wind Noise Management	●	●	●	●	●
Transient Noise Reduction	4 options	3 options	3 options	2 options	–
Binaural Noise Management	●	●	–	–	–
Feedback Cancellor					
Strength control	●	●	●	●	●
SoundTie 2					
iOS and Android direct streaming	●	●	●	●	●
Hands-free communication for iOS	●	●	●	●	●
Binaural coordination					
NFMI	●	●	●	●	●
Binaural Volume and Program Change	●	●	●	●	●
Non-Telephone Ear Control	●	●	●	●	●
Programming options					
General	●	●	●	●	●
Fitting bands	24	20	18	14	12
Environments	13	12	12	10	8
Manual listening programs	4	4	4	4	4
HiFi Music	●	●	●	●	–
Airplane	●	–	–	–	–
Data Logging	●	●	●	●	●
Adaptation Manager	●	●	●	●	●
CROS compatibility	●	●	●	●	●

HearLink 9030|7030|5030|3030|2030 MNB T R instruments can be programmed with HearSuite 2022.2.0 or higher

Operating conditions of miniBTE T R

Temperature: +5°C to +40°C (41°F to 104°F)

Humidity: 5% to 93%, non-condensing

Atmospheric pressure: 700 hPa to 1060 hPa

Storage and transportation conditions:

Temperature and humidity shall not exceed the below limits for extended periods during transportation and storage

Transport:

Temperature: –20°C to +60°C (–4°F to 140°F)

Relative humidity: 5% to 93%, non-condensing

Atmospheric pressure: 700 hPa to 1060 hPa

Storage:

Temperature: –20°C to +30°C (–4°F to 86°F)


Relative humidity: 5% to 93%, non-condensing

Atmospheric pressure: 700 hPa to 1060 hPa

Charger, miniBTE T R – Overview

Charger, miniBTE T R

The charger for HearLink miniBTE T R uses inductive technology that allows contactless charging of two hearing instruments via induction coil. Furthermore, the magnetic connection in the charger prevents the hearing instruments from falling out. When the hearing instruments are inserted into the charger, it automatically starts charging. The hearing instruments turn ON when they are removed from the charger.



Packaging set

- Travel pouch
- User Guide
- Power supply plug

Charging time of lithium-ion battery

- 3.5 h = Fully charged
- 1 h = 40 % charged
- 30 min = 20 % charged

¹⁾ Power plug will vary from country to country
* USB 2.0 high power (500 mA output) required

Charger, miniBTE T R – Technical data

Charger, miniBTE T R

Designed for/compatibility	HearLink miniBTE T R
Dimensions	Ø95 mm / total height of 39 mm
Weight	135 grams (5 oz)
Color	Black
Power supply plug	USB A
Status indications	LED on charger indicates Charger ON/OFF status LED on hearing instrument indicates charging status
Charging time of hearing instruments	Max 3.5 hours depending on initial state of the battery (Temperature: +10 °C to +35 °C (+50°F to +95°F)) Max 5 hours depending on initial state of the battery (Temperature: +5 °C to +10 °C (+41°F to +50°F)) / +35 °C to +38 °C (+95°F to +100°F)
Power source	Supplied power supply unit
Input voltage	5 V DC
Input current	< 0.2 A (charging two hearing instruments) <10mA stand-by (no hearing instruments inserted)
Cable	Fixed mounted cable / 150 cm
Connected to external equipment	When connected to external equipment plugged into a wall outlet, this equipment must comply with IEC-62368 (or IEC-60065, IEC-60950 until June 20, 2019) or equivalent safety standards.

Conditions of use

Operating conditions	Temperature: +5 °C to +38 °C (+41°F to +100°F) Relative humidity: 5% to 93 %, non-condensing
Storage and transportation conditions	Temperature: –25 °C to +70 °C (–13°F to +158°F) Relative humidity: 5% to 93 %, non-condensing
Atmospheric pressure	700 hPa to 1060 hPa

Technical data: Power supply unit

Power supply unit	AN05x – 050A
Input voltage	100 – 240 V AC
Input current	0.2 A
Input frequency	50 – 60 Hz
Output voltage	5 V DC
Output current	1 A



Manufacturer

SBO Hearing A/S
Kongebakken 9
DK-2765 Smørum
Denmark

hearingsolutions.philips.com

IP68

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. and are used under license. This product has been manufactured by or for and is sold under the responsibility of SBO Hearing A/S, and SBO Hearing A/S is the warrantor in relation to this product.